

Insulated Adjustable Wrenches



PRODUCT DESCRIPTION

All tools shown are manufactured and tested in accordance to BS EN60900:2012, with most tools where available being sourced from Insulated Tools Limited, who are the only company to use Nylon 11 for the protective covering, providing greater durability in harsh conditions. Each tool is tested to 10,000 volts and rated for use up to 1000 volts a.c. and 1500 volts d.c. for live line working. Tools supplied are marked in accordance to the requirements of BS EN60900:2012. In some instances tools may also be marked VDE which indicates those products which are manufactured by companies who are also accredited to the VDE Association in Germany.

Thumbnail	Network Rail Reference	Description
	0111/108698	Adjustable wrench 6"/150mm - maximum jaw opening 20mm (insulated up to 1000V BS EN 60900)
	0039/087304	Adjustable wrench 8"/200mm - maximum jaw opening 24mm (insulated up to 1000V BS EN 60900)
	0111/108699	Adjustable wrench 10"/250mm - maximum jaw opening 28mm (insulated up to 1000V BS EN 60900)
	0050/217156	Adjustable wrench 12"/300mm - maximum jaw opening 35mm (insulated up to 1000V BS EN 60900)
	0039/087306	Adjustable wrench 15"/375mm - maximum jaw opening 45mm (insulated up to 1000V BS EN 60900)
	URLT/018625	Adjustable wrench 18"/450mm - maximum jaw opening 60mm (insulated up to 1000V BS EN 60900)

SPECIFICATION