

## Insulated Screwdrivers - Pozidrive



### PRODUCT DESCRIPTION

All tools shown are manufactured and tested in accordance to BS EN60900:2012, with most tools where available being sourced from Insulated Tools Limited, who are the only company to use Nylon 11 for the protective covering, providing greater durability in harsh conditions. Each tool is tested to 10,000 volts and rated for use up to 1000 volts a.c. and 1500 volts d.c. for live line working. Tools supplied are marked in accordance to the requirements of BS EN60900:2012. In some instances tools may also be marked VDE which indicates those products which are manufactured by companies who are also accredited to the VDE Association in Germany.

Thumbnail	Network Rail Reference	Description
	0039/087199	Screwdriver Pozidrive No. 0 x 75mm Overall length 150mm (insulated up to 1000V BS EN 60900)
	0050/217146	Screwdriver Pozidrive No.1 x 75mm Overall length 152mm (insulated up to 1000V BS EN 60900)
	0039/087201	Screwdriver Pozidrive No.1 x 200mm Overall length 280mm (insulated up to 1000V BS EN 60900)
	0050/217147	Screwdriver Pozidrive No.2 x 100mm Overall length 203mm (insulated up to 1000V BS EN 60900)
	0050/217148	Screwdriver Pozidrive No.3 x 150mm Overall length 253mm (insulated up to 1000V BS EN 60900)

### SPECIFICATION