

Insulated Adjustable Torque Wrench Kit for Fishbolts



PRODUCT DESCRIPTION

Developed with Network Rail to enable the torque tightening of fishbolts, including those in check rail positions where access is limited in third rail areas.

Thumbnail	Network Rail Reference	Description
	0094/003077	Insulated adjustable torque wrench kit for fishbolts
	Comprises:	
	0094/008030	Insulated adjustable torque wrench range 100 - 475Nm Graduations at 100, 118, 150, 200, 220, 250, 300, 340, 420 and 475Nm With 22mm dia. male spigot Manufactured and tested to BS8020:2011
	0094/003078	Insulated check rail extension piece 1.5/8" AF open end With 22mm female spigot adaptor Manufactured and tested to BS8020:2011
	0094/003079	1" square drive x 22mm female non reversible ratchet head
	0094/003080	1.5/8" AF x 1" square drive bi-square socket
	0094/008033	Insulated release tool for end fittings Manufactured to BSEN60900
	0094/003081	Storage bag

SPECIFICATION

- Insulated for use in live line areas.
- Torque wrench graduated scale has positions hi-lighted for the tightening of fishbolts.
- Secure attachment of socket to ratchet head preventing accidental loss of socket while working or carrying to site.
- Open ended attachment (check rail end fitting) for tightening fishbolts where space is limited.

