

Insulated Handles/Breaker Bar



PRODUCT DESCRIPTION

These insulated handles can be used with a wide variety of end fittings and also ratchet heads, therefore provide an alternative solution to standard spanners and ratchets for engineers working in areas where live conductor rails may be present.

Thumbnail	Network Rail Reference	Description
	0094/008038	Insulated handle/breaker bar 400mm long with 22mm male spigot
	0094/008035	Insulated handle/breaker bar 600mm long with 22mm male spigot (supplied with 16mm to 22mm adaptor 0094/008031)
	0094/008037	Insulated handle/breaker bar 600mm long with 22mm male spigot
	Accessories for lock rod adjustment	
	0094/008057	11/16" Whitworth flared ring end fitting x 22mm, for use with 0094/008030 - lock rod adjustment
	0094/008058	7/8" Whitworth flared ring end fitting x 22mm, for use with 0094/008030 - lock rod adjustment
	0094/008059	50mm open ended fitting x 22mm, for use with 0094/008030 - lock rod adjustment
	General Accessories	
	0094/008031	16mm to 22mm spigot adaptor
	0094/008032	1/2" square drive ratchet head

SPECIFICATION

- Insulated to 1000V, manufactured to BS8020:2011
- 22mm male spigot enables the use of end fittings and ratchet heads
- Part number 0094/008035 supplied with 22mm to 16mm, enabling smaller sized end fittings of up to 1.5/16", 32mm and 1/2" square drive ratchet heads to be used.